



Koch Filter Corporation
Filtration Products Crafted with Pride

Multi-Pleat™ GT-HD

Heavy-Duty Pleated Panel Air Filters for Gas Turbine Applications



• MERV 8 performance rating (ASHRAE Test Standard 52.2-2007)

- Superior performance
- Two synthetic media options
- Durable .056" beverage-board frame construction
- Heavy-duty expanded metal backing
- Inserts available for pad holding frames
- Engineered versatility

The **Multi-Pleat™ GT-HD** is a heavy-duty pleated panel filter designed for use in gas turbine applications where filter durability and extended life are of primary concern. The Multi-Pleat GT-HD pleated air filter is designed with extended filter life to offer superior performance in the most extreme conditions. Its heavy-duty construction helps to insure product stability, high dust holding capacity, and low pressure drop in many gas turbine applications.

Heavy-duty construction

The Multi-Pleat GT-HD uses a heavy .056" beverage-board frame, which is twice as thick as normal pleated filters on the market. The heavier frame helps maintain the filter's integrity throughout its service life, even in high moisture applications. High-loft synthetic media is bonded to a rust resistant heavy-duty expanded metal backing which helps maintain the pleat structure to ensure full media utilization during operation.

Two media options

To meet the wide variety of applications found in today's gas turbine systems, Multi-Pleat GT-HD is available with two media alternatives. The standard media, GT-HD1, provides an excellent combination of efficiency, low resistance to airflow, and high dust holding capacity. The upgrade option, GT-HD3, is an ideal choice for applications where even longer filter life and higher efficiencies are required.

Both medias are available in unframed "media-only" elements upon request.

Multi-Pleat GT-HD Technical Data

Actual Size HxWxD	GT-HD1 Initial Resistance 2000/2500 CFM (in. w.g.)	GT-HD3 Initial Resistance 2000/2500 CFM (in. w.g.)	Final Recommended Resistance (in. w.g.)
233/8 x 233/8 x 33/4	.30/.42	.40/.58	1.50
231/4 x 231/4 x 4*	.30/.42	.40/.58	1.50
Average Arrestance:	61%	89%	

* The 4" exact depth replaces Pneumafil® OEM size specification. Brand names used for product identification purposes only.



Corporate Offices
P.O. Box 3186 • 625 West Hill Street (40208)
Louisville, KY 40201 • 502.634.4796
Fax: 502.637.2280 • E mail: info@kochfilter.com
www.kochfilter.com



Look for the Koch Green icon! Whenever you see the Koch Green icon, we are identifying a product that meets or exceeds our criteria in one or more of the following categories: Earns LEED Points, Reduces Energy Costs, Extends Filter Lifecycles, Conserves Resources, and Improves Indoor Environmental Quality.