

# Multi-Test Rigid

## Extended surface replacement filter



- Fits Aerosolve\* original equipment frames
- MERV 7, 12 and 16 performance rating (ASHRAE Test Standard 52.2-2007)
- Efficiency 55%, 85% and 95%
- Superior dust holding capacity
- High efficiency microfiberglass media

### Multi-Test Rigid Cartridges

Sizes	Efficiency Average Atmospheric			Capacity CFM	Effective Media Area Sq. Ft.	Pressure Drop						Face Velocity FPM
	MT45	MT85	MT95			MT45		MT85		MT95		
						IPD	Final	IPD	Final	IPD	Final	
12 x 24 x 12 (B)	45 - 55	80 - 85	93 - 97	500	21	.16"	.70"	.25"	.80"	.50"	1.00"	250
24 x 24 x 12 (A)	45 - 55	80 - 85	93 - 97	1000	43	.16"		.25"	.80"	.50"	1.00"	250
12 x 24 x 24 (E)	45 - 55	80 - 85	93 - 97	900	43	.40"		.45"	.80"	.55"	1.00"	450
24 x 24 x 24 (D)	45 - 55	80 - 85	93 - 97	1800	86	.40"		.45"	.80"	.55"	1.00"	450

\*For Product Identification Purposes Only.

Performance data is based on ASHRAE Test Standards 52.1-1999 and 52.2-2007.



#### Regional Sales Offices/Distribution Centers

Atlanta, GA • Detroit, MI • East Greenville, PA\* • Houston, TX\*  
Indianapolis, IN • Kansas City, MO • Louisville, KY\* • Madbury, NH  
Miami, FL • Nashville, TN • Mira Loma, CA\* • Tacoma, WA

\*Denotes manufacturing site.



**KOCH FILTER**

8401 Air Commerce Drive, Louisville, KY 40219  
Phone: 502.634.4796 | Fax: 502.637.2280  
info@kochfilter.com | www.kochfilter.com