

SPEC# \_\_\_\_\_

QUANTITY \_\_\_\_\_

application: **DROP-IN REPLACEMENTS**

models:

## 19 1/2" Cartridges



The 3M line of drop-in cartridges are an economical way to help reduce constituents in water that can cause equipment damage and unappealing product. Media choices of graded porosity, charge modified, activated carbon and pleated polypropylene provide a wide range of particulate holding capacities, chlorine reduction capabilities and micron ratings. These cartridges can be used in the 3M Water Filtration Products premium line of drop-in housings or as retrofits to upgrade current filtration.

### PRODUCT SPECIFICATIONS

Model Number	Part Number	Micron Rating	Claims	Flow Rate gpm (lpm)	Type	Qty Req'd	3M Housings
CFS8504-B	55847-05	10	Particulate Reduction	12 (45.4)	Uniform Density	1	CFS12 CFS02 CFSBCI-2 CFSBCI-3
CFS110	56121-11	5	Particulate Reduction	8 (30.3)	Progressive Porosity	2	
CFS124	56212-05	25	Course Particulate Reduction	6 (22.7)	Progressive Porosity	2	
CFS420IMF	55609-01	5	Particulate, Scale Inhibition	8 (30.3)	Graded Density Polyphosphate	2	
CFS2502	55603-18	0.6	Cyst Reduction	6 (22.7)	Pleated Membrane	1	
CFS2507	55757-04	5	5 Micron Absolute Particulate Reduction	6 (22.7)	Pleated Membrane	1	
CFSFSR-5	55603-20	5 Absolute	Fine Silt Reduction	6 (22.7)	Pleated Polypropylene	1	
CFSFSR-10	55603-21	10 Absolute	Fine Silt Reduction	6 (22.7)	Pleated Polypropylene	1	
CFS117	55593-04	5	Chlorine Taste and Odor Reduction	3 (11.4)	Granular Activated Carbon	2	
CFS117-S	55594-12	5	Chlorine Taste and Odor Reduction, Scale Inhibition	3 (11.4)	Granular Activated Carbon Polyphosphate	2	

# 19 1/2" Cartridges

# 3M™ Water Filtration Products

SPEC# \_\_\_\_\_

QUANTITY \_\_\_\_\_

MODEL NUMBER \_\_\_\_\_

PART NUMBER \_\_\_\_\_

## IMPORTANT: INSTALLATION TIPS

These installation tips are for informational purposes only and are not intended to be used as actual installation instructions. **CAUTION: To reduce the risk associated with property damage due to water leakage:**

- **Read and follow** Use Instructions before installation and use of this system.
- Installation and use **MUST** comply with all state and local plumbing codes.
- **Protect from freezing**, remove filter cartridge when temperatures are expected to drop below 40°F (4.4°C).
- **Do not install on hot water supply lines.** The maximum operating water temperature of this filter system is 100°F (37.8°C).
- **Do not install** where water hammer conditions may occur. If water hammer conditions exist you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for this condition.
- The disposable filter cartridge **MUST** be replaced every 12 months, at the rated capacity or if a noticeable reduction in flow rate occurs.

**⚠ WARNING: To reduce the risk associated with the ingestion of contaminants:**

- **Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.**

Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. EPA Establishment #070595-CT-001

3M Purification Inc. recommends regularly scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold. 3M Purification Inc. shall not be liable for system failures due to improper maintenance.



**3M Purification Inc.**  
400 Research Parkway  
Meriden, CT 06450 U.S.A.  
Toll Free: 866.990.9785  
Worldwide: 203.237.5541  
Fax: 203.238.8701  
www.3Mfoodservice.com  
www.3Mpurification.com