

3M™ Water Filtration Products

SPEC# _____

QUANTITY _____

application: **DROP-IN REPLACEMENTS**

models:

20" High Flow Cartridges



The 3M™ Water Filtration Products line of high flow cartridges for large diameter housings are an economical way to help reduce constituents in water that can cause equipment damage and unappealing product. Media choices of graded density, spun polyfiber, carbon block and pleated polypropylene provide a wide range of sediment holding capacities, chlorine reduction capabilities and micron ratings. These cartridges can be used in the 3M Water Filtration Products premium line of large diameter housings or as retrofits to upgrade current filtration.

PRODUCT SPECIFICATIONS

Model Number	Part Number	Micron Rating	Claims	Flow Rate gpm (lpm)	Type	CUNO Housings
CFS210-2	56189-07	5	Sediment Reduction	Up to 45 gpm (170 lpm)	Graded Density	CFS22 CFS22-1.5
CFS211-2	56189-09	25	Medium Sediment Reduction		Pleated Polyester	
CFS212-2	FSPSCCP20BB	20				
CFS214-2	55994-10	50	Coarse Sediment Reduction	Composite Wound		
CFS0215-2	55898-07	5	Chlorine Taste and Odor Reduction	Up to 10 gpm (38 lpm)	Modified Carbon Block	



20" High Flow Cartridges

3M™ Water Filtration Products

SPEC# _____

QUANTITY _____

MODEL NUMBER _____

PART NUMBER _____

IMPORTANT: INSTALLATION TIPS

These installation tips are for informational purposes only and are not intended to be used as actual installation instructions. **CAUTION:** To reduce the risk associated with property damage due to water leakage:

- **Read and follow** Use Instructions before installation and use of this system.
- Installation and use **MUST** comply with all state and local plumbing codes.
- **Protect from freezing**, remove filter cartridge when temperatures are expected to drop below 40°F (4.4°C).
- **Do not install on hot water supply lines.** The maximum operating water temperature of this filter system is 100°F (37.8°C).
- **Do not install** where water hammer conditions may occur. If water hammer conditions exist you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for this condition.
- The disposable filter cartridge **MUST** be replaced every 12 months, at the rated capacity or if a noticeable reduction in flow rate occurs.

⚠ WARNING: To reduce the risk associated with the ingestion of contaminants:

- **Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.**

CUNO Incorporated recommends regularly scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold. CUNO shall not be liable for system failures due to improper maintenance.

LIMITED WARRANTY

CUNO Incorporated warrants this Product (excluding disposable filter cartridge(s)) to be free from defects in material and workmanship for five (5) years from the date of purchase. The disposable filter cartridge is warranted from defects in material and workmanship for a period of one (1) year from the date of purchase. This warranty does not cover failures resulting from abuse, misuse, alteration or damage not caused by CUNO or failure to follow installation and use instructions. If the Product is defective CUNO will replace the Product or refund your Product purchase price. CUNO will not be liable for any indirect, special, incidental, or consequential damages arising from the use of this Product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you. To obtain warranty service, mail your request to Warranty Claims, CUNO Incorporated, 400 Research Parkway, Meriden, CT 06450. Proof of purchase (original sales receipt) must accompany the warranty claim, along with a complete description of the Product, model number and alleged defect. This warranty gives you specific legal rights and you may have other rights which vary from state to state, or country to country.