

Retrofit Cartridges for Competitive Systems

3M Water Filtration



3M™ Retrofit Cartridges Range

The 3M Water Filtration line of filtration products are carefully designed to protect beverage equipment, provide consistent beverage quality, and ensure seamless beverage service.

3M Water Filtration retrofit cartridges upgrade the performance of existing competitive systems with the same premium performance and design characteristics.

The cartridge design offers simple change outs while minimising corrosion potential often seen in metallic housings.

The sanitary quick change design minimises contamination of the filtration media, while the compact design allows the unit to be installed conveniently behind the beverage unit or under a cabinet.

The housing is durable and shatter-resistant, minimising the potential for leaks.

System materials are FDA, CFR-21 compliant for use in food and beverage applications. Cartridges are 3rd party certified for design and performance.

Premium carbon technologies are available for differing water conditions.

Features	Benefits
Graded density, compressed carbon block	Does not require activation Extends contact time for maximum chlorine and sediment reductions
Chlorine taste and odour reduction	Enhances beverage quality over the life of the filter
Built-in scale inhibition (Retrofits for Hot Bev only)	Protects equipment from the harmful effects of hard water Provides seamless beverage service
Micron ratings from 0.5 to 5	Maximum protection, long life and enhances beverage clarity



3M™ Retrofit Cartridges Range and Technical Specifications

Model	Part No.	Size	Micron Rating	Capacity litres	Flow Rate lpm	Claims					Replaces** (Everpure System)	
						Chlorine taste & odour	Sediment	Cyst	Turbidity	Scale Inhibition		Scale Reduction
Cold Beverage												
CS-25	70020017409	S	0.5	7,571	3.8	X	X	X	X			2C/4C
CFS9812X ^A	70020002666	L	0.5	34,069	5.7	X	X	X	X			MC
CFS9812ELX	70020018498	E	0.5	52,996	6.3	X	X	X	X			MC/XC
CFS9106	70020017367	S	1	9,450	3.8	X	X					2C/4C
CFS9112 ^A	70020002567	L	1	37,854	5.7	X	X					MC
CFS9710	7002002559	S	5	7,571	5.7	X	X					2C/4C
CS-65	70020017193	S	5	9,085	3.8	X	X					2C/4C
CFS9720 ^A	70020017136	L	5	18,170	5.7	X	X					MC/2CB5/4CB5
Hot Beverage												
CS-24	70020017391	S	0.5	7,571	3.8	X	X	X	X	X		BH/4H
CFS9812X-S ^A	70020002674	L	0.5	34,069	5.7	X	X	X	X	X		MH/L-2000
CFS9812ELX-S ^A	70020018506	E	0.5	52,996	6.3	X	X	X	X	X		MH/L-4000
CS-14	70020017375	S	1	9,450	3.8	X	X			X		BH/4H
CFS9112-S ^A	70020017219	L	1	37,854	5.7	X	X			X		MH/L-2000
CFS9710-S ^A	70020002542	S	5	7,571	5.7	X	X			X		BH
CS-64	70020017185	S	5	9,085	3.8	X	X			X		4H
CFS9720-S ^A	70020017128	L	5	18,170	5.7	X	X			X		MC/2CB5-S/4CB5-S
Drop ins												
CFS9005-IMF ^A	70020007871	–	N/A	N/A	5.7					X		IMF
CFS110-C20 [*]	70020143597	–	5	N/A	N/A		X					Pre-Filter
Special												
EP Plug	FD000049995	–	N/A	N/A	N/A							Plug
Empty Sanitising	70020115047	–	N/A	N/A	N/A							Sanitising Cartridge
SWC9135	70020015429	–	N/A	1,350 grains hardness capacity	1.91						X	750

* Suitable for Dual Port Filtration

** May not be a direct comparison in micron rating

S = Short sump(8'), L = Long sump(12'), E = Extended sump(18')

A = Product is ACS approved

Installation Tips:

- Shut off downstream equipment prior to installation of the system.
- Do not exceed operating parameters for temperature or pressure.
- Do not install outdoors.
- For cold water use only.
- For commercial use only.
- To have maximum operating pressure of 125 psi and operating temperature of 38°C.

Do not install with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 070595-CT-001. All materials are FDA compliant with CFR title 21.

3M Water Filtration recommends scheduled maintenance and replacement of the filter cartridge(s) in order for the product to perform as advertised/sold.



Water Filtration
3M United Kingdom plc
 3M Centre,
 Cain Road, Bracknell
 Berkshire RG12 8HT
 Tel: 0845 602 5237
 Fax: +44 (0) 1344 858559
 www.3M.eu/purification

3M Ireland
 The Iveagh Building,
 The Park,
 Carrickmines,
 Dublin 18
 Tel: 1800 320 500

14801
 Please recycle. Printed in UK.
 © 3M 2012. All rights reserved.
 LITFSEUR0028 0212